

File: S656
S600L
ULC G5.2
CCF7

29 September 2015

STANDARDS BULLETIN 2015-25

Amendment to Standard

Second Edition of CAN/ULC-S656-14 including Amendment 1

Standard for Oil-Water Separators

ULC Standards is pleased to announce the publication of Amendment 1 to the Second Edition of CAN/ULC-S656-14, Standard for Oil-Water Separators. Amendment 1 has been approved by the ULC Standards Committee on Oil-Water Separators and has been published under the date of September 2015.

Amendment 1 provides venting requirements for oil-water separators installed in buildings.

This Standard provides minimum requirements for shop fabricated single-wall or double-wall oil-water separators intended to collect and separate free oil from water by gravity separation at an inlet free oil concentration not exceeding 2 000 mg/L. These oil-water separators are also installed for the capture and retention of oil spills under dry weather conditions up to the free oil retention capacity of the oil-water separator. These oil-water separators are intended for installation and operation in accordance with, but not limited to, the following:

- A. Manufacturer's instructions;
- B. CCME Environmental Code of Practice for Aboveground and Underground Storage Tank Systems Containing Petroleum and Allied Petroleum Products;
- C. CPPI Code of Practice for Management of Water Effluent Quality at Petroleum Storage and Distribution Facilities; and
- D. Regulations of the authority having jurisdiction.

If you require any additional information, please contact John Wade at 613.755.2729 ext. 61426 or by email at John.Wade@ul.com.

This Standard can be ordered for \$270.00 CAN (Hardcopy) or \$225.00 CAN (PDF) from the ULC Standards website at www.ulc.ca and select *ULC Standards*. Once on the ULC Standards homepage, select *Sales of ULC Standards Materials* for further details.

Yours truly,

ULC Standards



G. Rae Dulmage
Director, Standards Department